

Next Generation ALE Concepts

W. Furman / E. Koski
Harris Corporation
RF Communications Division
Rochester, New York, U.S.A.



- **Important Dates:**

Abstracts Due: 15 February 2009

Draft Papers Due: 19 April 2009

Author Notification: 14 June 2009

Final Camera Ready Papers Due: 2 Aug 2009

- HF Session (?) - Info wfurman@harris.com

Overview



- History of ALE
- Comparison of 2G and 3G ALE
- How can ALE be improved?
- Summary
- References

History 1980-1985



- First ALE Systems in early 80s
 - Collins Selscan®
 - Harris Autolink®
 - Sunair Scancall®
- Mitre hired by Gov't in 1982 to Investigate interoperability problems and determined:
 - US Gov't could use existing assets much better (SHARES)
 - Gov't needed 2nd Generation ALE standard
- “Mitre Scheme” developed
 - Based on 3 existing systems, plus enhancements
 - Many new features
 - “Stairway to Heaven”

History 1985-1990



- Gov't and industry became highly polarized in 1985
 - USA, FEMA, Harris on Mitre waveform
 - USAF, NCS, Collins on Selscan
- Linking performance testing 1988
- Mitre waveform performed significantly better across all channel conditions
- MIL-STD-188-141A ALE released as a result in Sep 88 [1]
- FED-STD-1045 released in Sep 90[2]

History 1995-2009



- Mid 1990s NATO develops HF House concept
- Key component of HF House was ARCS
- Initial thought is to base improved ALE protocol on robust 75 bps waveform defined in 110A and STANAG 4415 [3]
- Harris develops and implements a burst serial tone waveform on IR&D used for Link Setup
- Harris develops code-combining based ARQ systems
- MIL-STD 188-141B Appendix C defined based on these concepts[4]
- ARCS develops into STANAG 4538 [5]and is based on a variation of these concepts

-
- Many mature products conforming to 188-141A(B) ALE (2G) Fielded
 - Virtually all new professional radios have embedded 2G ALE
 - A number of manufacturers have invested in 3G technology as defined in STANAG 4538.
 - To date many thousands of radios deployed with users utilizing 3G ALE
 - Automated systems use ALE for media access control
 - Very few proprietary systems fielded

2G / 3G Comparison



Characteristic	2G ALE	3GALE
Link Time	15.3s -3 character call sign	8.4s (Average values [6])
Link Robustness	0dB(3kHz BW)(0dB PAPR)	-8dB(3kHz BW)(4dB PAPR)
Waveform	8-FSK – 125 sym/s	8-PSK – 2400 sym/s
Main mode of Operation	Asynchronous	Synchronous Asynchronous Supported
Link Protection	Y – Not widely used	Y – Widely used
Channel Evaluation	LQA & Traffic Monitor	LQA & Traffic Monitor
Real Time Channel Evaluation (RTCE)	N	N
Listen Before Transmit	Y	Y
Adaptive / Cognitive	N	N

- Linking Time
 - Time to establish radios linked on a propagating frequency
 - Depends on synchronization approach
- Frequency management
 - Establishment of frequency / channel set
 - Can be based on prediction programs or experience
 - Geographical location of stations, required capacity, length of deployment all impact the number of frequencies needed
- Channel selection
 - Selection of frequency channel to use for communication
 - Can be based on prediction
 - Can be based on RTCE
 - Can be based on user communications history
 - Can be based on channel interference – Listen Before Transmit

How can ALE be improved?



- Faster Linking times
 - Decrease overhead, increase capacity
- Frequency Management
 - Employ cognitive radio concepts
 - Dynamically use unused frequencies
 - Improved Listen Before Transmit
- Channel Selection
 - Real Time selection just before use
 - Accurate signal quality estimates
- Wider bandwidth support
 - 6,12,24 KHz channels being defined in 141B

- 2G ALE
 - Employs a fast asynchronous scan coupled with a long link establishment transmission on the desired frequency. The transmission is long enough to capture the scanning receiver and begin the handshake on the desired frequency
- 3G ALE
 - Employs a slower synchronous scan coupled with a short link establishment transmission on the desired frequency. However as the system is synchronous the system must wait for the desired frequency dwell to happen. With a dwell time of 1.35 seconds this delay can have a significant impact.

- Faster scan
 - 2G - RC QuickCall
 - 3G - Harris HCMac
 - Moderate improvement
- Parallel Receivers
 - Dedicated receiver for each channel/frequency
 - Link time can be reduced as the system does not need to capture the scanning receiver (2G) or wait for the desired frequency slot to come up
 - Large system / HW impact
 - Significant Improvement

Frequency Management



- Frequency planning usually based on set of assigned frequencies. Planning tools available that allow user to plan a mission and “fill” a deployment of radios with required channel information.
- Missions may be planned significantly prior to deployment

- Fill sets based on Time of day (Night/Day)
- Deterministic pseudo-random allocation of pooled frequencies [7]

- Cognitive radio concepts
 - Modify frequency set in real time
 - Explore unused frequencies based on propagation prediction or between known propagating frequencies
 - Use improved Listen Before Transmit techniques to detect signaling on all channels
 - Frequency set based on assigned + cognitive frequencies
 - Protocol must be modified to announce new cognitive frequencies to the network, preferably in a robust minimal impact manner.
 - Power management considerations
 - Regulatory issues

-
- Most ALE systems, both 2G and 3G utilize ranking techniques to maintain a quality metric on each channel / destination.
 - Most ALE systems, both 2G and 3G utilize some sounding or Link Quality Analysis (LQA) signaling to occasionally or periodically update these quality metrics
 - Previous work has shown that Real Time Channel Evaluation provides performance / capacity gains by performing a quick quality analysis on all channels just prior to use [8][9]
 - The Harris Fast ALE System of the early 1990s successfully implemented RTCE and Linking[10]

- Improved Estimation and detection techniques
 - Improved channel quality estimation techniques can be used to provide estimates of SNR, multipath delay spread and Doppler spread using transmitted probe
 - Improved LBT Techniques can be used to monitor frequencies when not in use [11]
 - Performance of these techniques limited by observation time
- Multi-channel probe link establishment
 - Link establishment signaling sent serially or in parallel on multiple frequencies can be used to probe the channel list just before use (RTCE)
 - A parallel receiver structure can be used to minimize synchronization time
 - ALE Link Setup process needs to include identification of selected channel to establish link on

Wider Bandwidth



-
- Wider bandwidth channels being defined in MIL-STD-188-141C
 - Both 2G ALE and 3G ALE are 3kHz SSB systems
 - Need to consider how ALE would work in different bandwidths
 - Should adaptive bandwidth systems be considered?

- ALE systems required due to the propagation / interference complexities of HF links
- Many 2G and 3G ALE systems have been successfully deployed
- Opportunities exist for further improvements:
 - Faster linking times
 - Cognitive radio concepts
 - More accurate channel characterization
 - More accurate signal detection
 - Wider Bandwidth systems

References



- [1] MIL-STD-188-141A: Interoperability and Performance Standards for Medium and High Frequency Radio Systems.
- [2] U.S. Federal Standard 1052, Telecommunications: HF Radio Modems. Prepared by National Communications Systems Office Of Technology and Standards. Published by General Services Administration.
- [3] NATO STANAG 4415, Characteristics Of A Robust, Non-hopping, Serial Tone Modulator/Demodulator For Severely Degraded HF Radio Links.
- [4] MIL-STD-188-141B: Interoperability and Performance Standards for Medium and High Frequency Radio Systems.
- [5] STANAG 4538, "Technical Standards for an Automatic Radio Control System (ARCS) for HF Communication Links", Edition 1, North Atlantic Treaty Organization, 2000.
- [6] "Initial Performance Results from an Implementation of the STANAG 4538 Fast Link Setup Protocol", Michael A. Wadsworth and Eric A. Peach, Proceedings of the Nordic Shortwave Conference, HF01.
- [7] "Advanced HF Spectrum Management Techniques", N.P. Arthur, I.D. Taylor, K.D. Eddie, Proceedings of the Nordic Shortwave Conference, HF07.
- [8] "The Significance Of Real Time Frequency Selection." , W. N. Furman and D.D. McRae, Proceedings of the IEE Fifth International Conference on HF Radio Systems And Techniques. Edinburgh, Scotland, July 1991.
- [9] "On Fast Automatic Link Establishment". T. Willink and W. N. Furman. Proceedings of the IEE special colloquium on HF Link Establishment Techniques. February, 1996.
- [10] "Automated HF Data Delivery Utilizing Real Time Frequency Selection and Adaptive Data Link Protocol." W. N. Furman. Proceedings of the IEE Sixth International Conference on HF Radio Systems and Techniques, University Of York, U.K. July 1994.
- [11] "Advanced Listen Before Transmit Capabilities" William N. Furman Proceedings of the Nordic Shortwave Conference, HF04